

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization
International Bureau



(43) International Publication Date
12 January 2006 (12.01.2006)

PCT

(10) International Publication Number
WO 2006/004327 A1

(51) International Patent Classification⁷: H04R 25/02

(21) International Application Number:
PCT/KR2005/001846

(22) International Filing Date: 16 June 2005 (16.06.2005)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
10-2004-0052145 30 June 2004 (30.06.2004) KR

(71) Applicant and

(72) Inventor: JANG, Soon Suck [KR/KR]; Department of information, Control and, Instrumentation Engineering, ChoSun University., #375 Seoseok-dong,, Dong-gu Gwangju, 501-759 (KR).

(74) Agent: YANG, Gun Sik; MyungJi B/D., 5F. 1572-12, Seocho-dong, Seocho-gu, Seoul 137-874 (KR).

(81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM,

AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KM, KP, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NG, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SM, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW


(84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IS, IT, LT, LU, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:

— with international search report

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(54) Title: DIGITAL HEARING AID ENHANCING DIRECTIONAL PERFORMANCE



(57) Abstract: A digital hearing aid enhancing a directional performance for a patient who suffers from sole-ear hearing impairments is provided, in which the digital hearing aid cell inserted into one healthy ear is electrically connected with another digital hearing aid cell called an ear cell including a microphone worn in the other troubled ear, via an external electric wire. Two digital hearing aid cells are connected with each other via signal, power, and ground wires to thereby adjust a time delay parameter and thus make a time delay effect between the two microphones, so that a wearer who wears the digital hearing aid can better hear sound which comes from the side opposing the healthy ear, that is, from the troubled ear side.

WO 2006/004327 A1